
## OG22 SEATED ROW

#### PRODUCT GUIDE





#### PRODUCT FEATURES

- Effective and safe exercise equipment
- Adjustable loading:
  - o 5-150 kg (2 x weight unit)
  - o 2,5 kg increments
- Multigrip
- Adjustable seat (height)
- Adjustable chest support (distance)
- Grip bar for unilateral exercises
- Maintenance-free
- Can be installed on a movable platform

#### COLOR OPTIONS

The product comes as standard in RAL Classic colors: RAL 5012 (blue), RAL 3020 (red), RAL 6018 (green) RAL 1017 (yellow), or RAL 7024 (grey).



Other RAL colors are available at an additional cost.



# OG22 SEATED ROW

#### DIMENSIONS

| Length           | 1694 mm                 |
|------------------|-------------------------|
| Width            | 1515 mm                 |
| Height           | 999 mm                  |
| Equipment weight | 258kg (2 x weight unit) |

#### MATERIAL

| Metal parts      | Steel                   |
|------------------|-------------------------|
| Movement Arm     | Stainless steel         |
| Tube Strengths   | 3-6 mm                  |
| Coating solution | Zink and powder coating |
|                  | electropolishing        |

#### COUNTRY / STANDARD

| Country of manufacture | Finland |
|------------------------|---------|
| Standard               | EN16630 |


#### BASE OPTIONS

| A. Concrete | Surface mounting to concrete  |
|-------------|-------------------------------|
| B. Platform | Installed on movable platform |

#### FOUNDATION

For example: artificial turf or moldable safety platform Concrete min 120 mm below equipment Ground frost insulation, thickness based on the ground

Instruction guide included in delivery: installation instructions, maintenance, usage info. Contact: info@omnigym.com





### EN16630

# OMNIGYM